

TECHNICAL SPECIFICATION

LED Lamp

LEDCOB PAR16 E14



Technical data

- Nominal voltage: 230V / 50-60Hz
- Nominal wattage: 7W
- Rated luminous flux: 560lm
- Colour temperature:
 - 4000K – white
 - 2700K – warm white
- Colour rendering index: Ra≥80
- Beam Angle: 40°
- Warm-up time (60 %): Instant
- LED type: COB
- Light source: Epistar Taiwan
- Base: E14
- Average Lifetime: 30 000h
- Number of switching cycles: > 20000
- Dimmable: No
- Power factor: $\lambda > 0.80$
- Starting time: < 0.50s
- Lamp mercury content: 0.0mg


Product benefits

- Lower maintenance cost thanks to longer lifetime
- Reduced operational cost thanks to lower energy consumption
- Mercury free
- Maximum resistance to switching loads
- Correct operation even at low temperature
- Instant-on light

Areas of application


- All domestic rooms, especially where the lamps are visible
- Directional light sources
- Outdoor applications only in suitable luminaires
- Direct and indirect lighting
- Accent lighting

Variants and dimensions



Watt	Colour	LED chip lumens (lm) / LED(pcs)	LED lamp lumens (lm)	Colour temp. (K)	Size (mm)		Catalogue number	Packing (pcs)
					Length	Diameter		
7W	white	700 / 1	560	4000	75	50	99LED654	100
7W	warm white	700 / 1	560	2700	75	50	99LED655	100

Energy efficiency



Barcodes

Barcode	Catalogue number
3800131187161	99LED654
3800131187178	99LED655

Standards

EN 55015

EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-4; EN 61000-4-5; EN 61000-4-8; EN 61000-4-11

EN 61547

EN 62560

